



Amendment under 37 C.F.R. § 1.111
U.S. Application No. 10/799,882

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application:

LISTING OF CLAIMS:

1. (currently amended) A case comprising:

a containing part ~~adapted~~ operative to contain objects, said containing part comprising a front face, a rear face, at least two side faces and a bottom face which opposes an opening portion, and

a lid part provided on ~~an~~ said opening portion of said containing part via a hinge part, ~~and said lid part operable to be freely opened~~ open and closed ~~close~~ said opening portion,

wherein a pair of engagable, interlocking portions are positioned ~~adjacent~~ closer to corners of ~~respective openings~~ said opening portion of the lid part and the containing part than to middle portions of said opening portion of said lid part and said containing part, and wherein ~~each of~~ said pair of interlocking portions includes a lid part projection engagable with a respective container part projection, and

wherein said lid part projection is formed on an inner surface of said lid part, such that said lid part projection projects towards an inside of said lid part,

wherein said lid part projection does not have an undercut.

2. (currently amended) The case as set forth in claim 1, wherein a distance of each of said interlocking portions from a said front face of said case is less than or equal to ~~about~~ one-fourth of a width of each side face ~~of said case~~ in a horizontal direction.

3. (currently amended) The case as set forth in claim 1, further comprising locking portions provided in substantially middle ~~areas~~ portions of ~~both each of the side faces of the~~ openings of the containing part and the lid part, or ~~in areas near~~ adjacent to corners at a ~~back side~~ said rear face of said containing part.

Claim 4 (canceled)

5. (currently amended) The case as set forth in claim 1, wherein said ~~projection~~ projections ~~includes have~~ a rectangular shape ~~in view of~~ a cross section along a vertical axis thereof.

6. (currently amended) A case for storing at least one object, said case comprising:
a containing part ~~adapted~~ operative to store said at least one object, said containing part comprising a front face, a rear face, at least two side faces and a bottom face which opposes an opening portion;

a lid part that is connected to ~~an~~ said opening portion of said containing part via a hinge provided at a rear side of the case an upper portion of the rear face; and

locking portions, each comprising a first projection on said containing part and a second projection on said lid part, said first projection being engaged with said second projection when said ~~case~~ lid part is in a closed position,

wherein said locking portions are positioned ~~substantially near~~ closer to upper front corners of said containing part and ~~substantially near~~ lower front corners of said lid part than to middle portions of said containing part and said lid part.

7. (currently amended) The case as set forth in claim 6, wherein said ~~projection~~ includes projections have a rectangular shape in view of a cross section along a vertical axis thereof.

8. (currently amended) The case of claim 6, wherein said container part is stepped on ~~its~~ upper sides of said front face and said side faces to form thin side parts, and said first projection of said locking portions is ~~on~~ provided at a front corner portion of said thin side parts.

9. (currently amended) The case of claim 8, wherein upper edges of said thin side parts slope downward ~~continuously~~ from said rear ~~side~~ face of said case.

10. (original) The case of claim 8, wherein a height of said thin parts is one of constant and variable.

Claim 11 (canceled)

12. (currently amended) The case of claim 6, wherein said hinge comprises a first hinge part and a second hinge part, a said first hinge part of said hinge is substantially spaced along an upper rear edge of said rear face of said containing part and an upper rear edge of said lid part, and a said second hinge part of said hinge is not spaced along at least one of said upper rear edge of said rear face of said containing part and said upper rear edge of said lid part.

13. (currently amended) The case of claim 6, wherein a width and a height of said first projection is at least substantially equal to a width and a height of said second projection.

14. (currently amended) The case of claim 6, wherein widths of at least one of said first projection and said second projection are at least substantially greater than heights of at least one of said first projection and said second projection, respectively.

15. (currently amended) A case for storing at least one object, said case comprising:
a containing part ~~adapted~~ operative to store said at least one object, said containing part comprising a front face, a rear face, at least two side faces and a bottom face which opposes an opening portion;

a lid part that is connected to ~~an~~ said opening portion of said containing part via a hinge provided at a rear side an upper portion of said rear face of the case; and

means for producing a locking force ~~substantially near~~closer to upper front corners of said containing part and lower front corners of said lid part, than to middle portions of said containing part and said lid part, when said case is closed,

wherein said means for producing comprises locking portions, each comprising a first projection on said containing part and a second projection on said lid part, said first projection being engaged with said second projection when said lid part is in a closed position, said locking portions being positioned closer to said upper front corners of said containing part and said lower front corners of said lid part than to said middle portions of said containing part and said lid part, and

wherein said second projection is formed on an inner surface of said lid part, such that said second projection projects towards an inside of said lid part.

Claim 16 (canceled).

17. (currently amended) The case as set forth in claim ~~16~~15, wherein said ~~projection~~ includes projections have a rectangular shape in ~~view of~~ a cross section along a vertical axis thereof.

18. (currently amended) The case of claim ~~16~~15, wherein a width and a height of said first projection is at least substantially equal to a width and a height of said second projection.

19. (currently amended) The case of claim ~~16~~15, wherein widths of at least one of said first projection and said second projection are at least substantially greater than heights of at least one of said first projection and said second projection, respectively.

20. (currently amended) The case of claim ~~16~~15, wherein said container part is stepped on ~~its~~ upper sides of said front face and said side faces to form thin side parts, and said first projection of said locking portions is ~~on~~ provided at a front corner portion of said thin side parts.

21. (currently amended) The case of claim 20, wherein upper edges of said thin side parts slope downward ~~continuously~~ from said rear ~~side face~~ face of said case.

22. (original) The case of claim 20, wherein a height of said thin parts is one of constant and variable.

Claim 23 (canceled).

24. (currently amended) The case of claim 15, wherein said hinge comprises a first hinge part and a second hinge part, said ~~a first hinge part of said hinge is substantially~~ spaced along an upper ~~rear~~ edge of said rear face of said containing part and an upper rear edge of said lid part, and a second hinge part ~~of said hinge~~ is not spaced along at least one of said upper ~~rear~~ edge of said rear face of said containing part and said upper rear edge of said lid part.

Amendment under 37 C.F.R. § 1.111
U.S. Application No. 10/799,882

25. (currently amended) The case of claim 1, wherein widths of at least one of said lid part projection and said container part projection are at least substantially greater than heights of at least one of said lid part projection and said container part projection, respectively.